



PILSEN-TYPE WATER DISTILLER

TE-2801

Used in the process of water purification.

Technical Characteristics

TE-2801

- Conductivity: up to 5.0 $\mu\text{S} / \text{cm}$ (considering input conductivity 310 $\mu\text{S} / \text{cm}$);
- Yield: ± 10 liters / hour;
- Consumption: ± 100 liters / hour;
- Safety: in the absence of water, automatic shutdown;
- Boiler: unique sealing system of the boiler without the use of screws, which provides convenience in disassembly;
- Control box: in carbon steel with anti-corrosion treatment and electrostatic painting;
- Structure: polished 304 stainless steel;
- Dimensions: L = 400 x d=330 x H=1080 mm;
- Weight: 10kg;
- Power: 7100W;
- Voltage: 220 Volts;
- ACCOMPANY: - 05 screws with bushing - Bracket for fixing - Instruction Manual and warranty term ;

Benefits and Advantages

- Control box in order to house the components as well as protect them from probable moisture coming from leaks, ensuring safety and durability
- Electrical protection through bipolar circuit breaker for equipment protection preventing damage to components and users in the process and in the electrical supply
- 304 stainless steel vat dyes and distillation tube for longer shelf life
- 304 stainless steel armored resistance for durability
- Protection system against overheating due to lack of water, ensuring safety
- Lid with retractable sealing ring that allows its removal for easy internal cleaning of the tub
- Strict quality control, in which checks and tests ensure the perfect operation of the equipment, providing safety and customer satisfaction
- Customer service, to answer questions and provide explanations about the equipment and methodologies.