



# ***SUGAR DETERMINATOR – REDUTEC***

***TE-0861***

Used for the determination of reducing sugars in foods and beverages such as sugarcane juice fruits tomato extract candies etc.

## Technical Characteristics

### TE-0861

- Supply: Semi-automatic by solenoid valve;
- Temperature control: Analog;
- Turning point: Visual;
- Security: Built-in boiler;
- Glassware: Bowl /Boiler made of borosilicate glass;
- Cabinet: In carbon steel with anti-corrosive treatment and electrostatic paintin;
- Dimensions: W=220 x D=340 x H=650 mm;
- Weight: 5 kg;
- Power: 1500 Watts;
- Voltage: 220 Volts;
- ACCOMPANIES: - 01 rod - 01 tweezers for burette - 02 extra fuses - Instruction Manual with Warranty Term;

## Benefits and Advantages

- Semi-automatic supply by solenoid valve which ensures greater process control
- Lighting system for viewing the boiler water level avoiding exceeding the maximum level
- Opening for viewing the boiler water level easy to check the moment of replenishment
- Stainless steel structure with anticorrosive treatment and electrostatic painting increasing the time of equipment life
- Optional: burette developed specifically for this type of application avoiding its handling close to hot steam greater security for the analyst
- Steam formation system through a built-in glass boiler which improves the transfer of heat inside and speeds up the temperature change time also attributing greater safety for the analyst
- Gives greater security to the user as it replaces manually mounted systems that do not have built-in boiler system
- Less use of glassware
- Vapor rate variation (boiling) at 10 levels by potentiometer
- Ergonomic clip to secure the burette
- Presence of relief: steam outlet directed to the bowl when it is closed or boiler cleaning when it's open
- Ease of changing the bowl in case of maintenance
- Ease of removing the boiler for cleaning or maintenance.

## Related Products

