



BAIN-MARIE WITH WATER CIRCULATION

TE-056-MAG

Used in various types of laboratory analysis heating solutions and samples in general where the use of temperatures to boiling is required.

Technical Characteristics

TE-056-MAG

- Temperature: Ambient +7°C to 100°C;
- Temperature Controller: Microcontrolled Digital;
- Sensor: PT-100;
- Control accuracy: $\pm 0,3^{\circ}\text{C}$;
- Uniformity: $\pm 0.3^{\circ}\text{C}$;
- Circulation: Internal by magnetic stirring;
- Safety: Thermal insulation between the Bowl and the cabinet;
- Tray and Bowl: In 304 stainless steel;
- Cabinet: Polystyrene and 304 stainless steel base with electrostatic coating;
- Bowl dimensions: W=500 x D=300 x H=150 mm;
- Bowl volume: 22 liters;
- Dimensions: W=600 x D=450 x H=340 mm;
- Weight: 12,8kg;
- Power: 1400 Watts;
- Voltage: 220 Volts +/-5%;
- Accompanies: - 01 Resistance protection tray - 01 Teflon-coated magnetic bar (little fish) - 01 Stainless steel cover with 6 reduction rings - 02 extra fuses - Instruction manual with warranty;

Benefits and Advantages

- Compact and easy-to-handle equipment
- Presence of predictive control that anticipates the control signal so that the system does not present high over shoot that is more homogeneous temperatures throughout the process
- Bowl in 304 stainless steel providing greater durability
- Thermal insulation in mineral wool blanket providing security
- Internal homogenization by magnetic stirring
- Controller that allows calibration of the equipment according to an external standard
- Input for external thermometer for calibration
- PT-100 sensor the most sensitive
- Clock/Timer: time up to 9999 minutes allows the operator to program the time the bath should keep warming up
- REC function – Recover: putting this parameter in On mode the last configuration is saved when the bath is turned on again it will start to heat up according to the previously configured value
- Bulb thermostat to protect against overheating or lack of water automatic shutdown that can only be turned back on by the user providing safety
- Presence of reducing rings on the lid allowing adaptation according to the container to be used providing practicality
- Option to be used with gallery and drip tray cover (acrylic or stainless steel)
- Rigid Quality Control in which checks and tests guarantee the perfect functioning of the equipment providing safety and client satisfaction
- Client service to answer questions and provide explanations about the equipment and methodologies
- Possibility of adaptations according to the client's needs makes the equipment already of line a special equipment.