

+55 (19) 2105-6161 comex@tecnal.com.br





# **ROTATING AGITATOR** TE-166

Used in the preparation of samples that require a 360° rotational movement.



João Leonardo Fustaino, nº 325 Distrito Industrial Uninorte Piracicaba/SP-Brasil • CEP 13.413-102



# **Technical Characteristics**

#### **TE-166**

- Rotation: 10 to 45 RPM;
- Accuracy: ±3 RPM;
- Rotation Control: Analog;
- Rotation Amplitude: 360°;
- Engine: 38 Watt Reducer;
- Capacity: 40 50ml Falcon tubes or customizable tests;
- Cabinet: In carbon steel with anti-corrosive treatment and electrostatic painting;
- Dimensions: W=730 x D=250 x H=430 mm;
- Weight: 7 kg;
- Power: 200 Watts;
- Voltage: 220 Volts;
- ACCOMPANIES: 02 extra fuses Instruction Manual with Warranty Term;

### Benefits and Advantages

- Promotes tube agitation without forming bubbles
- Easy operation adjusting rotation only
- Fully adjustable rotation angle
- It supports a greater number of tests compared to a similar model optimizing the shaking process
- Flexibility in choosing tubes
- Light and compact equipment
- Carbon steel cabinet with anti-corrosive treatment and electrostatic painting ensuring longer equipment life and ease of cleaning.

## **Related Products**



